



ULTRA FLEX

PRODUCT DATA SHEET

DATE: JUNE 2018

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product description

FAST ULTRA FLEX is a highly flexible, fibre reinforced, waterproofing compound.

Intended Uses

A quick and easy way of sealing waterproofing details such as roof screw bolts, cracked tiles, roof ridges, flashings, overlaps as well as repairing hail damaged and cracked acrylic and membrane waterproofing systems.

Features & Benefits

- Highly flexible.
- Squeeze and Seal.
- Excellent adhesion.
- Water based.

Product Information

Type	Waterproof Repair Gel (Membrane/fibre enhanced)
Appearance	Thick gel
Durability	Excellent
Colours	Grey
S G at 23°C	Approx.: 1, 28
Theoretical spreading rate	2,1ℓ/m ²
Practical spreading rate	The practical spreading rate will vary depending on the porosity and profile of the substrate, as well as the application technique and tools used.

Cautions

Do not apply if rain is imminent.
Do not use to overcoat existing bitumen systems.

Surface Preparation

Ensure that the surface is properly dry and in sound condition, free from dust, rust, grease, oil, algae, fungus or any loose and flaking particles.

Application Details

Mixing	Shake bottle well
Method	Squeeze bottle and apply
Thinning	Not recommended – Ready for use
Cleaning	Water
Drying time	Depends on film thickness, humidity and air temperature.
Recoating time	24 hours
Full cure	7 Days

- Shake bottle well.
- Unscrew the cap, gently squeeze the bottle applying a generous layer of the FAST ULTRA FLEX to the area required.
- Curing time depends on film thickness, humidity and air temperature.
- Do not apply if rain is imminent.
- Do not use to overcoat existing bitumen systems.
- Clean up with water.

Storage & Packaging

Store away from direct sun, heat and severe cold.
Packaging: 1ℓ

FAST

ULTRA FLEX

WATERPROOFING



Precautions

Not for internal consumption.

Keep out of reach of children.

Ensure good ventilation during application and drying.

In case of skin contact, wash with soap and water or a recognised skin cleaner.

Avoid contact with eyes – wear protective eye-ware. In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.

In case of ingestion, drink plenty of water. Do not induce vomiting. Seek medical attention immediately.

Refer to Material Safety Data Sheet for complete information.

Waste disposal: Dispose as for normal paint waste. Do not empty into drains or water courses

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest Technical Data Sheet is being used.