



GP PVA

PRODUCT DATA SHEET

DATE: NOVEMBER 2020

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product description

CREST GP PVA is a good quality Sheen Acrylic PVA.

Intended Uses

A durable Acrylic PVA with good hiding power for interior and exterior use.

Features & Benefits

- Tough and Durable
- Sheen finish
- Washable

Product Information

Type	Water-based Acrylic
Colour	White
Spreading rate	5-9m ² /ℓ depending on application.
Practical spreading rate	The practical spreading rate will vary depending on the porosity and profile of the substrate, as well as the application technique and tools used.
S G at 23°C	Approx.: 1,45
Flash point	Non-flammable

Cautions

Do not apply direct to bare metal surfaces.
Do not paint during wet or cold (below 10°C) weather.
Drying time will be extended during cold or wet weather conditions. Do not paint on high gloss enamel.



Surface Preparation

Surface must be clean and dry before painting.

Concrete/Cement/Plaster Walls

Apply two coats un-thinned.

Wallboards/Ceiling boards

No primer required except on bare metal areas (nail heads).

Gypsum Plaster

Prime surface with PLASTER PRIMER.

Previously painted surfaces

Surfaces must be in sound condition.

Application Details

Method	Brush or roller
Thinning	Not recommended
Cleaning	Water
Touch Dry:	1 hour
Re-coating Time	4 hours (2 coats required)

Storage & Packaging

Store away from direct sun, heat and severe cold.
Packaging: 5ℓ & 20ℓ

Safety Precautions

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognised skin cleanser.
- Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.

- Harmful if swallowed. Do not induce vomiting. Drink plenty of water. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information.

WASTE DISPOSAL

Dispose as for normal paint waste.

Do not empty into drains or water courses.

DISCLAIMER

Products are manufactured to stringent specifications under laboratory-controlled conditions. Application methods are beyond our control. All information is issued as a guide to the use of the product(s) concerned. Whilst Fast International endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot (because Fast International has no direct or continuous control over where and how Fast International products are applied) accept any liability either directly or indirectly arising from the use of Fast International products, whether or not used in accordance with any advice, specification, recommendation, or information given by the company. The purchaser of the product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s) and assumes all risks and liabilities in connection therewith.