



PLASTER PRIMER

PRODUCT DATA SHEET

DATE: NOVEMBER 2020

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product description

CREST PLASTER PRIMER is an Alkaline resistant primer for brick, plaster, concrete, cement, and gypsum. It is a water-based primer and sealer for interior and exterior use. Over-coat with a wide range of topcoats such as alkyds, vinyl, and water-based paints.

Intended Uses

An Alkaline resistant water-based plaster primer for interior and exterior use on walls and ceilings.

Features & Benefits

- 100% Water-based and safe to use.
- Environmentally friendly.
- Matt finish.
- Quick drying.
- Excellent re-coating properties.
- Interior and Exterior use.
- Low odour.
- Lead free.

Product Information

Type	Water based alkali-resistant solution polymer
Appearance	Matt finish
Colour	White
Spreading rate	6-8m ² /ℓ depending on application.
Practical spreading rate	The practical spreading rate will vary depending on the porosity and profile of the substrate, as well as the application technique and tools used.



Tint Bases	None
S G at 23°C	Approx.: 1,35
Flash point	Non-flammable

Cautions

Do not paint during wet or cold (below 10°C) weather. Drying time will be extended during cold or wet weather conditions.

Surface Preparation

Ensure surface is in dry and sound condition, free from dust, grease, oil, algae, fungus, or any loose particles before painting.

All surfaces must be completely dry, and moisture contents must be less than 8%.

NEW WORK

Cement plaster, concrete, unglazed brickwork, fibre-cement, ceiling boards:

Remove any loose particles and laitance by most suitable means. N.B. Soft, under bound, friable, and highly porous surfaces must be restored to a sound condition.

PREVIOUSLY PAINTED SURFACES

Previously painted surfaces in sound condition:

Remove loose and flaking paint back to a sound substrate and a firm edge by scraping and sanding. Spot prime bare areas with appropriate primer. Clean with FAST SUGAR SOAP to remove all contaminants. Rinse with clean water to remove all traces of SUGAR SOAP. Proceed as for new work.

CREST

PLASTER PRIMER

INTERIOR / EXTERIOR



Previously painted surfaces in poor condition:

Completely remove paint by most appropriate means e.g. scraping, coarse sanding or stripping with FAST PAINT STRIPPER. Wash thoroughly with FAST SUGAR SOAP. Rinse with fresh water. Proceed as for new work.

Chalky surfaces:

Remove as much of the chalky surface as possible. Seal with CREST PLASTER PRIMER WATERBASED and allow drying for 4 hours. Proceed as for new work.

FILLING

Fill defects with FAST LIQUID CRACKFILLER OR FAST CRACKFILLER and prime. Fill fibre cement with FAST FILL and prime.

Application Details

Method	Brush or roller
Thinning	Not recommended
Cleaning	Water
Touch Dry:	1 hour
Re-coating Time	4 hours (2 coats required)

Storage & Packaging

Store away from direct sun, heat and severe cold.
Packaging: 5ℓ & 20ℓ

Safety Precautions

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognised skin cleanser.
- Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist.
- Harmful if swallowed. Do not induce vomiting. Drink plenty of water. Seek medical attention.
- Refer to Material Safety Data Sheet for complete information.

WASTE DISPOSAL

Dispose as for normal paint waste.
Do not empty into drains or water courses.

DISCLAIMER

Products are manufactured to stringent specifications under laboratory-controlled conditions. Application methods are beyond our control. All information is issued as a guide to the use of the product(s) concerned. Whilst Fast International endeavours to ensure that any advice, recommendation, specification or information is accurate and correct, the company cannot (because Fast International has no direct or continuous control over where and how Fast International products are applied) accept any liability either directly or indirectly arising from the use of Fast International products, whether or not used in accordance with any advice, specification, recommendation, or information given by the company. The purchaser of the product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s) and assumes all risks and liabilities in connection therewith.