



BENZINE

PRODUCT DATA SHEET

DATE: JUNE 2017

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product description

FAST BENZINE is a clear hydrocarbon solvent, used as a cleaning agent for fats and oils.

Recommended uses

- It is used widely in adhesives where the drying rate needs to be slower than that of hexane.
- It is used for domestic & industrial cleaning & is a diluent in paints, lacquers & inks.
- It is used widely in the rubber industry as it has sufficient solvency to make rubber tacky, thereby creating a bond between the rubber layers.

PRECAUTIONS:

Storage

- Store out of reach of children and animals.
- Store in cool, dry place, away from any sources of heat.
- Store in original container.
- Keep out of direct sunlight.
- Ensure cap is tightly sealed and product is kept upright at all times.
- Dispose of empty container and do not use for any other purpose.
- Do not dispose product into common waste system.

Health and Safety instructions

- Use protective glasses. If contact with eyes occurs, flush open eyes with plenty of water and seek medical attention.
- Use protective gloves. If contact with skin occurs, wash with soapy water.
- If swallowed, rinse mouth with water and seek medical attention. Do not induce vomiting.
- Use a respirator. Do not inhale vapour. Use within well ventilated areas.
- If over exposed move victim to fresh air & seek medical attention.

- In the event of fire, use carbon dioxide foam or chemical powder to extinguish. Do not use water.

Warnings

- Harmful if swallowed.
- Skin and eye irritant.
- Not suitable for use on plastics and fibreglass.
- Do not apply to hot surfaces.
- Do not smoke when applying.

Pack sizes

- 750ml Bottle – 20 per case
- 5L Bottle
- 25L Container
- 200L Drum

Colour

- Clear

Specific Data

Appearance	Liquid
Colour	Colourless
Odour	Pungent
Solubility	Negligible
Boiling point	> 50°C
Flash point	< 0°C
Density @ 20°C	0.678 G/CM ³
Flammability	Flammable
Solvent Group	Aliphatic hydro carbon

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest Technical Data Sheet is being used.

FAST

BENZINE

SOLVENTS

